



Product Info

Brand: AM-R Series UPC: 85339906902 **UNSPSC: 39121324 Carton Quantity:** 1 Carton Weight: 3 lbs Carton Length: 7 in

Carton Width: 9 in

Carton Height: 9 in Country of Origin: United States of America

Color: Gray (RAL 7035)

Material: ULTRAGUARD® Fiberglass reinforced polyester -

compression molded SMC box and Cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

Box Features: Installation Type:

back side brass inserts

Enclosure Type: JIC Size Cover Type: Opaque Closure Type: 2-Screw

AM664RH

Availability:

Height: 6.1 in Width: 6.1 in **Depth:** 4.05 in

Usable Depth: 5.29 in Volume: 156 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

6"x6"x4" AM Series fiberglass wall mount enclosure

at 1-800-722-2679 or sales@alliedmoulded.com

For up-to-date delivery on this product, please contact us

Mounting Description: Stainless steel feet fastened to

assembly with raised 2-screw hinged cover

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





NARNING - PROP 65 Click here for more information!