



# **Product Info**

Brand: AM Series UPC: 85339906667 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 3 lbs Carton Length: 6 in Carton Width: 9 in Carton Height: 10 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and Cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## AM664T

6"x6"x4" AM Series fiberglass wall mount enclosure assembly with hinged cover and stainless steel twist latch **Availability:** 

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Opaque

Closure Type: Metal Twist Latch

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

Box Features:

Installation Type:

Height: 6.1 in

Width: 6.1 in

Depth: 4.05 in

Usable Depth: 3.76 in

Volume: 156 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

#### Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13;  $\underline{File\ No.\ E120175}$ 

Complies with: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive



WARNING - PROP 65 Click here for more information!