



AM743SF

7"x4"x3" AM Series fiberglass small junction box with 4-screw lift-off cover

Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: Small Junction

Cover Type: Opaque

Closure Type: 4-Screw Lift-Off

Box Features: Installation Type:

Height: 6.01 in Width: 3.31 in Depth: 3.13 in

Usable Depth: 3.06 in **Volume:** 71 cu in

Product Info

Brand: AM Series **UPC:** 85339910091 **UNSPSC:** 39121324

Carton Quantity: 1 Carton Weight: 2 lbs Carton Length: 4 in

Carton Width: 4 in Carton Height: 8 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

 $\textbf{Material:} \ \, \textbf{ULTRAGUARD} \, \textbf{\textit{\textbf{B}}} \ \, \textbf{\textit{\textbf{Fiberglass}}} \ \, \textbf{\textit{\textbf{reinforced}}} \ \, \textbf{\textit{\textbf{polyester}}} \, \textbf{\textit{\textbf{\textbf{-}}}}$

compression molded SMC box and Cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-

In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel fasteners and an formed in place polyurethane gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive





WARNING - PROP 65 Click here for more information!