



Product Info

Brand: AM-R Series UPC: 85339908975 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 6 lbs Carton Length: 7 in Carton Width: 9 in

Carton Height: 11 in **Country of Origin:** United States of America

Color: Gray (RAL 7035) with clear window

 $\begin{tabular}{ll} \textbf{Material:} ULTRAGUARD @ Fiberglass reinforced polyester-compression molded SMC box and cover with bonded clear \mathbb{R}^2 and \mathbb{R}^2 with bonded clear \mathbb{R}^2 and \mathbb{R}^2 with \mathbb{R}^2 and \mathbb{R}^2 with \mathbb{R}^2 and \mathbb{R}^2 with \mathbb{R}^2 wit$

polycarbonate window

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AM864RHW

8"x6"x4" AM Series fiberglass wall mount enclosure assembly with raised 2-screw hinged window cover

Availability:

Made to order; For up-to-date delivery on this product, please contact us at 1-800-722-2679 or

sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: 2-Screw

Mounting Description: Stainless steel feet fastened to

back side brass inserts

Box Features:

Installation Type:

Height: 8 in
Width: 6.13 in
Depth: 4.01 in
Usable Depth: 5.1 in

Volume: 203 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





