



AMEC3630123PTW

36"x30"x12" Empire Series fiberglass wall mount enclosure assembly with hinged window cover and stainless-steel 3-point latching handle

Availability:

Made to order; For up-to-date delivery on this product,

please contact us at 1-800-722-2679 or

sales@alliedmoulded.com

Enclosure Type: Wall Cabinets

Cover Type: Opaque with Viewing Window

Closure Type: 3-Point Handle

Mounting Description: Molded flange

Height: 36.5 in Width: 30.5 in Depth: 12.03 in Usable Depth: 12.48 in

Volume: 15062 cu in

Product Info

Brand: Empire Series UPC: 85339972280 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 79 lbs

Carton Length: 16 in Carton Width: 35 in Carton Height: 45 in

Country of Origin: United States of America **Color:** Gray (RAL 7035) with clear window

 $\begin{tabular}{ll} \textbf{Material:} ULTRAGUARD @ Fiberglass reinforced polyester-compression molded SMC box and cover with bonded clear \mathbb{R}^2 and \mathbb{R}^2 with bonded clear \mathbb{R}^2 and \mathbb{R}^2 with \mathbb{R}^2 and \mathbb{R}^2 with \mathbb{R}^2 and \mathbb{R}^2 with \mathbb{R}^2 wit$

polycarbonate window

Additional Materials: 316 stainless steel external hardware, Brass inserts, Plated carbon steel internal hardware, Polyurethane (FIP) Formed-In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a formed-in-place polyurethane gasket system.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





WARNING - PROP 65
Click here for more information!