



ALLIED  
MOULDED  
PRODUCTS, Inc.

419-636-4217  
222 N. Union St.  
Bryan, OH 43506



## Product Info

**Brand:** Empire Series

**UPC:** 85339972280

**UNSPSC:** 39121324

**Carton Quantity:** 1

**Carton Weight:** 79 lbs

**Carton Length:** 16 in

**Carton Width:** 35 in

**Carton Height:** 45 in

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035) with clear window

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

**Additional Materials:** 316 stainless steel external hardware, Brass inserts, Plated carbon steel internal hardware, Polyurethane (FIP) Formed-In-Place gasket system

## AMEC3630123PTW

36"x30"x12" Empire Series fiberglass wall mount enclosure assembly with hinged window cover and stainless-steel 3-point latching handle

### Availability:

**Made to order:** For up-to-date delivery on this product, please contact us at 866-283-9324 or [sales@alliedmoulded.com](mailto:sales@alliedmoulded.com)

**Enclosure Type:** Wall Cabinets

**Cover Type:** Opaque with Viewing Window

**Closure Type:** 3-Point Handle

**Mounting Description:** Molded flange

**Height:** 36.5 in

**Width:** 30.5 in

**Depth:** 12.03 in

**Usable Depth:** 12.48 in

**Volume:** 15062 cu in

### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a formed-in-place polyurethane gasket system.

### Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



 **WARNING - PROP 65**  
[Click here for more information!](#)