+91.80.67926666
NO.199 & 242, Road No. 8
Bommasandra, Jigani Link Road
Bangalore, Karnataka

AMHMI120ICCL

12"x10" HMI Cover Kit with hinged clear cover and stainless-steel snap latch

Availability:
For up-to-date delivery on this product, please contact us at 866-283-9324 or sales@alliedmoulded.com

Cover Type: Clear Polycarbonate

Closure Type: Metal Snap Latch

Mounting Description: 8 Screws

Height: 11.93 mm

Width: 10.15 mm

Depth: 0.96 mm

Usable Depth: 2.27 mm

Volume: 275 cu mm

Product Info

UNSPSC: 39121302

Carton Quantity: 1

Carton Weight: 1.814 kg

Carton Length: 127 mm

Carton Width: 355.6 mm

Carton Height: 355.6 mm

Country of Origin: United States of America

Color: Gray (RAL 7035) with clear cover

Material: Polycarbonate frame and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware, Polyurethane (FIP) Formed-In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost and longer life cycle cost compared to steel. Rigid design with a gasket system encased in a continuous channel on the cover and frame. Open back frame design with an opening size of 10.47″ x 8.69″ and is a UL recognized component for use with NEMA 4X enclosures. *Will fit Allied Moulded enclosure sizes 14”x12” and larger.

Application:

Cover and protect electrical and electronic controls including HMI (Human Machine Interface) instruments, touch pad controllers and pushbuttons mounted on the surface of NEMA 4X enclosures. No need to open the enclosure to view electronics or perform maintenance, decreasing arc flash risks and safety hazards.

Standards:

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; File No. E487574

UL® listed and recognized component for use with enclosure products Types 1, 2, 3, 3R, 4, 4X, 12 and 13.

Complies With:
1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive

c UL us
LISTED
ENCLOSURE ACCESSORY
E487574

⚠ **WARNING** – PROP 65
Click here for more information!