



AMHMI142CCH

14"x12" HMI Cover Kit with 2-screw hinged clear cover **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Cover Type: Clear Polycarbonate

Closure Type: 2-Screw

Mounting Description: 10 Screws

Height: 13.95 in Width: 12.07 in Depth: 0.96 in Usable Depth: 2.2 in

Volume: 370 cu in

Product Info

UPC: 85339991922
UNSPSC: 39121302
Carton Quantity: 1
Carton Weight: 5 lbs
Carton Length: 5 in
Carton Width: 16 in

Carton Height: 16 in

Country of Origin: United States of America **Color:** Gray (RAL 7035) with clear cover

Material: Polycarbonate frame and clear polycarbonate

cover

Additional Materials: 316 stainless steel external hardware, Polyurethane (FIP) Formed-In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost and longer life cycle cost compared to steel. Rigid design with a gasket system encased in a continuous channel on the cover and frame. Open back frame design with an opening size of 12.49" x 10.71" and is a UL recognized component for use with NEMA 4X enclosures. A *Will fit Allied Moulded enclosure sizes $16\hat{a}$? x14 \hat{a} ? and larger.

Application:

Cover and protect electrical and electronic controls including HMI (Human Machine Interface) instruments, touch pad controllers and pushbuttons mounted on the surface of NEMA 4X enclosures. No need to open the enclosure to view electronics or perform maintenance, decreasing arc flash risks and safety hazards.

Standards:

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; File No. E487574

UL® listed and recognized component for use with enclosure products Types 1, 2, 3, 3R, 4, 4X, 12 and 13.

Complies With:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive





WARNING - PROP 65 Click here for more information!