



# **Product Info**

UPC: 85339975380 UNSPSC: 39121302 Carton Quantity: 1 Carton Weight: 7 lbs Carton Length: 6 in Carton Width: 18 in Carton Height: 19 in Country of Origin: United States of America Color: Gray (RAL 7035) with clear cover

Material: Polycarbonate frame and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware, Polyurethane (FIP) Formed-In-Place gasket system

## AMHMI164CCH

16"x14" HMI Cover Kit with 2-screw hinged clear cover Availability:
For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com
Cover Type: Clear Polycarbonate
Closure Type: 2-Screw
Mounting Description: 10 Screws
Box Features:
Installation Type:
Height: 15.87 in
Width: 14.07 in
Depth: 0.96 in
Usable Depth: 2.2 in
Volume: 491 cu in

### Features:

Non-corrosive, non-conductive, light weight with lower installation cost and longer life cycle cost compared to steel. Rigid design with a gasket system encased in a continuous channel on the cover and frame. Open back frame design with an opeining size of 14.49" x 12.71" and is a UL recognized component for use with NEMA 4X enclosures.Å \*Will fit Allied Moulded enclosure sizes 18â[]?x16â[]? and larger.

### **Application:**

Cover and protect electrical and electronic controls including HMI (Human Machine Interface) instruments, touch pad controllers and pushbuttons mounted on the surface of NEMA 4X enclosures. No need to open the enclosure to view electronics or perform maintenance, decreasing arc flash risks and safety hazards.

#### Standards:

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; File No. E487574

UL® listed and recognized component for use with enclosure products Types 1, 2, 3, 3R, 4, 4X, 12 and 13.

Complies With: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive



