



AMHMI164HTP

16"x14" HMI Cover Kit with 2-screw (tamper-proof) hinged cover

Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Cover Type: Opaque

Closure Type: 2-Screw (Tamper-Proof)
Mounting Description: 10 Screws

Box Features: Installation Type:

Height: 15.87 in
Width: 14.07 in
Depth: 0.96 in
Usable Depth: 2.2 in

Volume: 491 cu in

Product Info

UPC: 85339975397
UNSPSC: 39121302
Carton Quantity: 1
Carton Weight: 7 lbs
Carton Length: 6 in
Carton Width: 18 in
Carton Height: 19 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

Material: Polycarbonate frame and cover

Additional Materials: 316 stainless steel external

hardware, Polyurethane (FIP) Formed-In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost and longer life cycle cost compared to steel. Rigid design with a gasket system encased in a continuous channel on the cover and frame. Open back frame design, UL recognized component for use with NEMA 4X enclosures. *Will fit Allied Moulded enclosure sizes 18â\[?x16\hat{a}\[?]? and larger.

Application:

Cover and protect electrical and electronic controls including HMI (Human Machine Interface) instruments, touch pad controllers and pushbuttons mounted on the surface of NEMA 4X enclosures. No need to open the enclosure to view electronics or perform maintenance, decreasing arc flash risks and safety hazards.

Standards:

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; File No. E487574

UL® listed and recognized component for use with enclosure products Types 1, 2, 3, 3R, 4, 4X, 12 and 13.

Complies With:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





Click here for more information!