



## AMHMI88L

8"x8" HMI Cover Kit with hinged cover and stainless-steel snap latch

## **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Cover Type: Opaque

Closure Type: Metal Snap Latch Mounting Description: 8 Screws

Box Features: Installation Type:

**Height:** 7.93 in **Width:** 8.15 in **Depth:** 0.96 in

Usable Depth: 2.27 in

# **Product Info**

UPC: 85339978435 UNSPSC: 39121302 Carton Quantity: 1 Carton Weight: 3 lbs Carton Length: 6 in Carton Width: 10 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

Carton Height: 11 in

Material: Polycarbonate frame and cover

**Additional Materials:** 316 stainless steel external

hardware, Polyurethane (FIP) Formed-In-Place gasket system

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost and longer life cycle cost compared to steel. Rigid design with a gasket system encased in a continuous channel on the cover and frame. Open back frame design with an opening size of  $6.47^{\circ}$  x  $6.69^{\circ}$  and is UL listed for use with Type 4X enclosures. \*Will fit Allied Moulded enclosure sizes  $10 \, \mathrm{agg}$ ? and larger.

## **Application:**

Cover and protect electrical and electronic controls including HMI (Human Machine Interface) instruments, touch pad controllers and pushbuttons mounted on the surface of Type 4X enclosures. No need to open the enclosure to view electronics or perform maintenance, decreasing arc flash risks and safety hazards.

#### Standards:

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; File No. E487574

UL® listed and recognized component for use with enclosure products Types 1, 2, 3, 3R, 4, 4X, 12 and 13.

Complies With:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





Click here for more information!