



Product Info

Brand: ULTRAPLUG®

UPC: 0.5

UPC: 85339995104

UNSPSC: 39121321

Carton Quantity: 1

Carton Weight: 0.069 lbs

Country of Origin: United States of America

Color: Gray (RAL 7035)

Patents: U.S. Patent No. 9,045,932

Material: Polycarbonate

Additional Materials: Blended neoprene/EPDM gasket

AMHS150

AMHS200 - ULTRAPLUG® enclosure hole plug
(2.500-2.750) - Light Gray

Availability:

For up-to-date delivery on this product, please contact us
at 866-283-9324 or sales@alliedmoulded.com

Trade Size Ref: 1-1/2" Conduit (1.984)

Plugged Hole Dia. Range: 2.000-2.187

Plug Diameter: 2.495

Plug Head Height: 0.235

Nut Height: 0.5

Features:

Plug fins are self centering, anti-rotational design for fast
and easy one person assembly and no-tools tightening

Application:

Capable of plugging unused holes in NEMA 4X enclosures
and designed to maintain applicable NEMA/UL/CSA
enclosure ratings

Standards:

Meets Requirements: ANSI/UL50, ANSI/UL50E, and
ANSI/UL508A; [File No. E487574](#)

UL® listed and recognized component for use with
enclosure products Types 1, 3, 3R, 4, 4X, and 12.

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



⚠ WARNING - PROP 65
[Click here for more information!](#)