



## Product Info

**Brand:** ULTRAPLUG®

**UPC:** 0.75

**UPC:** 85339995159

**UNSPSC:** 39121321

**Carton Quantity:** 1

**Carton Weight:** 0.302 lbs

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035)

**Patents:** U.S. Patent No. 9,045,932

**Material:** Polycarbonate

**Additional Materials:** Blended neoprene/EPDM gasket

## AMHS400

ULTRAPLUG® enclosure hole plug (4.500-4.750) - Light Gray

**Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or [sales@alliedmoulded.com](mailto:sales@alliedmoulded.com)

**Closure Type:**

**Box Features:**

**Installation Type:**

**Trade Size Ref:** 4" Conduit (4.641)

**Plugged Hole Dia. Range:** 4.500-4.750

**Plug Diameter:** 5.120

**Plug Head Height:** 0.235

**Nut Height:** 0.75

**Features:**

Plug fins are self centering, anti-rotational design for fast and easy one person assembly and no-tools tightening

**Application:**

Capable of plugging unused holes in NEMA 4X enclosures and designed to maintain applicable NEMA/UL/CSA enclosure ratings

**Standards:**

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; [File No. E487574](#)

UL® listed and recognized component for use with enclosure products Types 1, 3, 3R, 4, 4X, and 12.

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



**WARNING** – PROP 65

[Click here for more information!](#)