



Product Info

Brand: POLYLINE®
UPC: 85339974048
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 5 lbs
Carton Length: 8 in

Carton Width: 12 in Carton Height: 14 in

Country of Origin: United States of America **Color:** Gray (RAL 7035) with clear cover **Patents:** U.S. Patent No. 7,572,975

Material: Polycarbonate box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket

AMP1204CCF

12"x10"x4" POLYLINE® polycarbonate wall mount enclosure assembly with 4-screw lift-off clear cover **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate **Closure Type:** 4-Screw Lift-Off

Mounting Description: Nonmetal flange fastened to

back side brass inserts

Box Features: Installation Type: Height: 11.93 in

Width: 10.15 in **Depth:** 4.08 in

Usable Depth: 4.16 in **Volume:** 601 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters)

2. RoHS directive





WARNING – PROP 65 Click here for more information!