



# **AMP1226**

12"x12"x6" POLYLINE® polycarbonate wall mount enclosure assembly with 4-screw lift-off cover

#### **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size
Cover Type: Opaque

Closure Type: 4-Screw Lift-Off

Mounting Description: Nonmetal feet fastened to back

side brass inserts

Height: 11.93 in Width: 11.93 in Depth: 5.94 in Usable Depth: 6.06 in

Volume: 864 cu in

# **Product Info**

Brand: POLYLINE®

UPC: 85339985105

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 6 lbs

Carton Length: 8 in

Carton Width: 14 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

Carton Height: 14 in

**Patents:** U.S. Patent No. 7,572,975 **Material:** Polycarbonate box and cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Brass inserts, Plated carbon steel internal hardware, Polycarbonate mounting brackets, Polyurethane (FIP) Formed-In-Place gasket system

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

## **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; File No. E120175

#### Complies with:

1.  $\dot{\text{EN}}$  / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters)

2. RoHS directive





WARNING - PROP 65
Click here for more information!