



Product Info

Brand: POLYLINE®
UPC: 85339985198
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 6 lbs
Carton Length: 8 in
Carton Width: 14 in
Carton Height: 14 in
Country of Origin: United States of America
Color: Gray (RAL 7035) with clear cover
Patents: U.S. Patent No. 7,572,975
Material: Polycarbonate box and clear polycarbonate cover
Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Brass inserts, Plated carbon steel internal hardware, Polycarbonate mounting brackets, Polyurethane (FIP) Formed-In-Place gasket system

AMP1226CCF

12"x12"x6" POLYLINE® polycarbonate wall mount enclosure assembly with 4-screw lift-off clear cover

Availability:

For up-to-date delivery on this product, please contact us at 866-283-9324 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate

Closure Type: 4-Screw Lift-Off

Mounting Description: Nonmetal flange fastened to back side brass inserts

Height: 11.93 in

Width: 11.93 in

Depth: 5.94 in

Usable Depth: 6.06 in

Volume: 864 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; [File No. E120175](#)

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters)
2. RoHS directive



⚠ WARNING - PROP 65
[Click here for more information!](#)