



Product Info

Brand: POLYLINE® UPC: 85339993483 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 7 lbs Carton Length: 8 in Carton Width: 14 in Carton Height: 16 in Country of Origin: United States of America Color: Gray (RAL 7035) with clear cover

Patents: U.S. Patent No. 7,572,975

 $\label{eq:material:polycarbonate} \textbf{Material:} \ \textbf{Polycarbonate} \ \textbf{box} \ \textbf{and} \ \textbf{clear} \ \textbf{polycarbonate} \ \textbf{cover}$

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AMP1426CCH

14"x12"x6" POLYLINE® polycarbonate wall mount enclosure assembly with 2-screw hinged clear cover **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate

Closure Type: 2-Screw

Mounting Description: Nonmetal feet fastened to back side brass inserts

Box Features:

Installation Type:

Height: 13.85 in

Width: 12.07 in

Depth: 5.94 in

Usable Depth: 5.99 in

Volume: 1161 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; $\underline{\rm File}$ No. $\underline{\rm E120175}$

Complies with: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive



WARNING – PROP 65 Click here for more information!