



# AMP1648CCNL

 $16\mbox{"x}14\mbox{"x}8\mbox{" POLYLINE} \mbox{$\mathbb{R}$}$  polycarbonate wall mount enclosure assembly with hinged clear cover and nonmetal snap latch

## **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

**Enclosure Type:** JIC Size

**Cover Type:** Clear Polycarbonate **Closure Type:** Nonmetal Snap Latch

Mounting Description: Nonmetal feet fastened to back

side brass inserts

**Height:** 15.98 in **Width:** 13.98 in **Depth:** 7.81 in

**Usable Depth:** 8.27 in **Volume:** 1968 cu in

# **Product Info**

Brand: POLYLINE®

UPC: 85339991229

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 9 lbs

Carton Length: 10 in

Carton Width: 18 in

Carton Height: 20 in

**Country of Origin:** United States of America **Color:** Gray (RAL 7035) with clear cover **Patents:** U.S. Patent No. 7,572,975

Material: Polycarbonate box and clear polycarbonate cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Brass inserts, Plated carbon steel internal hardware, Polycarbonate mounting brackets, Polyurethane (FIP) Formed-In-Place gasket system

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

### **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive







Click here for more information!