



# **Product Info**

Brand: POLYLINE®
UPC: 85339985631
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 17 lbs
Carton Length: 11.25 in
Carton Width: 19 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

Carton Height: 22 in

**Patents:** U.S. Patent No. 7,572,975 **Material:** Polycarbonate box and cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket

system

## **AMP2060F**

20"x16"x10" POLYLINE  $\$  polycarbonate wall mount enclosure assembly with 4-screw lift-off cover

#### Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size
Cover Type: Opaque

Closure Type: 4-Screw Lift-Off

Mounting Description: Nonmetal flange fastened to

back side brass inserts

Box Features: Installation Type: Height: 19.76 in Width: 15.43 in

Depth: 10 in

**Usable Depth:** 9.95 in **Volume:** 3200 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

# **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive









Click here for more information!