



# **Product Info**

Brand: POLYLINE®
UPC: 85339934646
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 2 lbs
Carton Length: 5 in

**Carton Width:** 6 in **Carton Height:** 6 in

**Country of Origin:** United States of America **Color:** Gray (RAL 7035) with clear cover **Patents:** U.S. Patent No. 7,572,975

Material: Polycarbonate box and clear polycarbonate cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Polyurethane (FIP) Formed-In-Place gasket system

## AMP443CC

4"x4"x3" POLYLINE® polycarbonate wall mount enclosure assembly with 4-screw lift-off clear cover

## **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

**Enclosure Type:** JIC Size

**Cover Type:** Clear Polycarbonate **Closure Type:** 4-Screw Lift-Off

Mounting Description: Nonmetal feet fastened with

self-threading screws

Box Features: Installation Type:

Height: 4.09 in Width: 4.09 in Depth: 3.88 in

**Usable Depth:** 3.07 in **Volume:** 51.75 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

## **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; File No. E120175

### Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters)

2. RoHS directive





**WARNING** - PROP 65 Click here for more information!