



## Product Info

**Brand:** POLYLINE®  
**UPC:** 85339992882  
**UNSPSC:** 39121324  
**Carton Quantity:** 1  
**Carton Weight:** 2 lbs  
**Carton Length:** 6 in  
**Carton Width:** 8 in  
**Carton Height:** 8 in  
**Country of Origin:** United States of America  
**Color:** Gray (RAL 7035) with clear cover  
**Patents:** U.S. Patent No. 7,572,975  
**Material:** Polycarbonate box and clear polycarbonate cover  
**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## AMP664CCNL

6"x6"x4" POLYLINE® polycarbonate wall mount enclosure assembly with hinged clear cover and nonmetal snap latch

### Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

**Enclosure Type:** JIC Size

**Cover Type:** Clear Polycarbonate

**Closure Type:** Nonmetal Snap Latch

**Mounting Description:** Nonmetal feet fastened to back side brass inserts

### Box Features:

#### Installation Type:

**Height:** 6.03 in

**Width:** 6.26 in

**Depth:** 3.94 in

**Usable Depth:** 4.06 in

**Volume:** 177 cu in

### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

### Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; [File No. E120175](#)

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



**WARNING - PROP 65**

[Click here for more information!](#)

---