



### **Product Info**

Brand: POLYLINE®
UPC: 85339992905
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 2 lbs
Carton Length: 6 in

Carton Width: 8 in Carton Height: 8 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

**Patents:** U.S. Patent No. 7,572,975 **Material:** Polycarbonate box and cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket

system

# AMP664F

6"x6"x4" POLYLINE® polycarbonate wall mount enclosure assembly with 4-screw lift-off cover

### **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size
Cover Type: Opaque

Closure Type: 4-Screw Lift-Off

Mounting Description: Nonmetal flange fastened to

back side brass inserts

Box Features: Installation Type: Height: 6.03 in Width: 6.26 in

Depth: 3.94 in Usable Depth: 4.06 in

Volume: 177 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

# Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; File No. E120175

#### Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters)

2. RoHS directive





WARNING - PROP 65
Click here for more information!