



# **Product Info**

Brand: ULTRALINE® UPC: 85339959588 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 4 lbs Carton Length: 7 in Carton Width: 11 in Carton Height: 13 in Country of Origin: United States of America

**Color:** Gray (RAL 7035) with clear cover

**Patents:** U.S. Patent No. 7,572,975

Material: ULTRACHARD® Eiberglass reinford

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Brass inserts, Plated carbon steel internal hardware, Polycarbonate mounting brackets, Polyurethane (FIP) Formed-In-Place gasket system

# AMU1084CCLF

10"x8"x4" ULTRALINE  $\circledast$  fiberglass wall mount enclosure assembly with hinged clear cover and stainless-steel snap latch

### Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate

Closure Type: Metal Snap Latch

**Mounting Description:** Nonmetal flange fastened to back side brass inserts

Height: 10.05 in

Width: 8.27 in

Depth: 4 in

Usable Depth: 4.12 in

Volume: 416 cu in

#### **Features:**

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

#### Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13;  $\underline{\rm File}$  No.  $\underline{\rm E120175}$ 

Complies with: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive



WARNING - PROP 65 Click here for more information!