



Product Info

Brand: ULTRALINE®
UPC: 85339952428
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 8 lbs
Carton Length: 9 in

Carton Width: 15 in

Carton Height: 17 in
Country of Origin: United States of America
Color: Gray (RAL 7035) with clear window

Patents: U.S. Patent No. 7,572,975

 $\begin{tabular}{ll} \textbf{Material:} ULTRAGUARD @ Fiberglass reinforced polyester-compression molded SMC box and cover with bonded clear \\ \end{tabular}$

polycarbonate window

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AMU1426LW

14"x12"x6" ULTRALINE® fiberglass wall mount enclosure assembly with hinged window cover and stainless-steel snap latch

Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: Metal Snap Latch

Mounting Description: Nonmetal feet fastened to back

side brass inserts

Box Features:

Installation Type:

Height: 14.05 in **Width:** 12.27 in

Depth: 6 in

Usable Depth: 6 in Volume: 1207 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system

encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive









Click here for more information!