



Product Info

Brand: ULTRALINE®

UPC: 85339959939

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 12 lbs

Carton Length: 11 in

Carton Width: 18 in

Carton Height: 19 in

Country of Origin: United States of America

Color: Gray (RAL 7035) with clear window

Patents: U.S. Patent No. 7,572,975

Material: ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AMU1648TWF

16"x14"x8" ULTRALINE® fiberglass wall mount enclosure assembly with hinged window cover and stainless-steel twist latch

Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: Metal Twist Latch

Mounting Description: Nonmetal flange fastened to back side brass inserts

Box Features:

Installation Type:

Height: 16.05 in

Width: 14.27 in

Depth: 8 in

Usable Depth: 7.99 in

Volume: 2061 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; [File No. E120175](#)

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



WARNING - PROP 65

[Click here for more information!](#)