



# **Product Info**

Brand: ULTRALINE®
UPC: 085339978596
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 19 lbs
Carton Length: 12 in

Carton Width: 20 in Carton Height: 22 in

**Country of Origin:** United States of America **Color:** Gray (RAL 7035) with clear cover

Patents: U.S. Patent No. 7,572,975

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and clear polycarbonate cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

# AMU2060CCTF

20"x16"x10" ULTRALINE  $\$  fiberglass wall mount enclosure assembly with hinged clear cover and stainless-steel twist latch

### **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

**Cover Type:** Clear Polycarbonate **Closure Type:** Metal Twist Latch

Mounting Description: Nonmetal flange fastened to

back side brass inserts

**Box Features: Installation Type: Height:** 19.87 in

Width: 16.09 in Depth: 9.95 in

**Usable Depth:** 10.09 in **Volume:** 3517 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system

encased in a continuous channel on the cover.

## **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive





