



Product Info

Brand: ULTRALINE®
UPC: 85339952558
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 3 lbs
Carton Length: 7 in

Carton Width: 9 in Carton Height: 12 in

Country of Origin: United States of America **Color:** Gray (RAL 7035) with clear cover **Patents:** U.S. Patent No. 7,572,975

Material: ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AMU864CCLF

 $8"x6"x4" \ ULTRALINE \ fiberglass \ wall \ mount enclosure assembly with hinged clear cover and stainless-steel snap latch$

Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate **Closure Type:** Metal Snap Latch

Mounting Description: Nonmetal flange fastened to

back side brass inserts

Box Features: Installation Type: Height: 8.05 in

Width: 6.27 in Depth: 4 in

Usable Depth: 4.09 in **Volume:** 252 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive





