



# **Product Info**

Brand: ULTRALINE®
UPC: 85339952671
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 3 lbs
Carton Length: 7 in

Carton Width: 9 in
Carton Height: 12 in

**Country of Origin:** United States of America **Color:** Gray (RAL 7035) with clear window **Patents:** U.S. Patent No. 7,572,975

 $\begin{tabular}{ll} \textbf{Material:} ULTRAGUARD @ Fiberglass reinforced polyester-compression molded SMC box and cover with bonded clear \\ \end{tabular}$ 

polycarbonate window

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket

system

# AMU864LWF

8"x6"x4" ULTRALINE® fiberglass wall mount enclosure assembly with hinged window cover and stainless-steel snap latch

## **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

**Enclosure Type:** JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: Metal Snap Latch

Mounting Description: Nonmetal flange fastened to

back side brass inserts

Box Features: Installation Type:

Height: 8.05 in Width: 6.27 in Depth: 4 in

Usable Depth: 4 in Volume: 252 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system

encased in a continuous channel on the cover.

### **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive









Click here for more information!