



Product Info

Brand: ULTRALINE®
UPC: 85339985969
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 5 lbs
Carton Length: 7 in
Carton Width: 12 in

Carton Height: 13 in

Country of Origin: United States of America **Color:** Gray (RAL 7035) with clear cover **Patents:** U.S. Patent No. 7,572,975

 $\begin{tabular}{ll} \textbf{Material:} ULTRAGUARD @ Fiberglass reinforced polyester-compression molded SMC box and clear polycarbonate cover $$ $ (1.5) $$

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AMU884CC

8"x8"x4" ULTRALINE® fiberglass wall mount enclosure assembly with 4-screw lift-off clear cover

Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate **Closure Type:** 4-Screw Lift-Off

Mounting Description: Nonmetal feet fastened to back

side brass inserts

Box Features: Installation Type: Height: 7.98 in

Width: 8.2 in
Depth: 5.19 in

Usable Depth: 4.12 in Volume: 312 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; $\underline{\text{File No. }}$ $\underline{\text{E120175}}$

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





