



# AMU884CCNL

8"x8"x4" ULTRALINE® fiberglass wall mount enclosure assembly with clear cover and nonmetal snap latch **Availability:** For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

**Cover Type:** Clear Polycarbonate

Closure Type: Nonmetal Snap Latch

**Mounting Description:** Nonmetal feet fastened to back side brass inserts

**Box Features:** 

Installation Type:

Height: 7.98 in

Width: 8.2 in

Depth: 5.19 in

Usable Depth: 4.12 in

Volume: 312 cu in

# **Product Info**

Brand: ULTRALINE® UPC: 85339986140 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 5 lbs Carton Length: 7 in Carton Width: 12 in Carton Height: 13 in Country of Origin: United States of America Color: Gray (RAL 7035) with clear cover Patents: U.S. Patent No. 7,572,975

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

## **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; <u>File No. E120175</u>

Complies with: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive





