



AMU884CCNLF

8"x8"x4" ULTRALINE® fiberglass wall mount enclosure assembly with clear cover and nonmetal snap latch **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate **Closure Type:** Nonmetal Snap Latch

Mounting Description: Nonmetal flange fastened to

back side brass inserts

Box Features: Installation Type:

Height: 7.98 in **Width:** 8.2 in **Depth:** 5.19 in

Usable Depth: 4.12 in **Volume:** 312 cu in

Product Info

Brand: ULTRALINE®

UPC: 85339986157

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 5 lbs

Carton Length: 7 in

Carton Width: 12 in

Carton Height: 13 in

Country of Origin: United States of America **Color:** Gray (RAL 7035) with clear cover **Patents:** U.S. Patent No. 7,572,975

Material: ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; $\underline{\text{File No. E120175}}$

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





