



## **AMXL403212L3PT**

40x32x12 Control XL Series fiberglass wall mount enclosure assembly with hinged cover and stainless-steel 3-point latching handle

**Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or [sales@alliedmoulded.com](mailto:sales@alliedmoulded.com)

**Enclosure Type:** Wall Cabinets

**Cover Type:** Opaque

**Closure Type:** 3-Point Handle

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

**Height:** 39.73 in

**Width:** 31.23 in

**Depth:** 11.5 in

**Usable Depth:** 11.41 in

**Volume:** 14269 cu in

## **Product Info**

**Brand:** Control XL Series

**UPC:** 8533999804

**UNSPSC:** 39121324

**Carton Quantity:** 1

**Carton Weight:** 77 lbs

**Carton Length:** 17 in

**Carton Width:** 35 in

**Carton Height:** 44 in

**Country of Origin:** India

**Color:** Gray (RAL 7035)

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and Cover

**Additional Materials:** 316 stainless steel external hardware, Brass inserts, Plated carbon steel internal hardware, Polyurethane (FIP) Formed-In-Place gasket system

## **Features:**

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a formed-in-place polyurethane gasket system.

## **Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## **Standards:**

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; [File No. E120175](#)

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



**WARNING - PROP 65**

[Click here for more information!](#)

---