



Product Info

Brand: Vapor Seal UPC: 85339180111 UNSPSC: 39121308 Carton Weight: 9 lbs Carton Length: 17 in

Carton Width: 12 in Carton Height: 8 in

Country of Origin: United States of America

Color: Off white

Patents: U.S. Patent No. 6,908,003 B2 **Material:** Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Polyurethane

flange, Polyvinyl chloride clamps

5305-NKV

Five gang electrical box for use with nonmetallic sheathed

cable

Carton Quantity: 6

Mounting Description: Angled mid nails

Box Type: Wall - Switch/Receptacle

Box Features: Air-sealed flange (energy efficient), Nails,

Speed "K" nonmetallic clamps

Installation Type: New Work

Height: 3-3/4 in Width: 9-5/16 in Depth: 3-9/16 in Volume: 94 cu in Number of Gangs: 5

Features:

Machine tapped device holes, slot provision for low voltage divider, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures,

Speed "K" Clamps factory installed

Application:

New work residential construction 2 HR fire resistive walls – air-sealed electrical boxes for envelope walls in Energy Star homes, UL approved for back-to-back installation

Standards:

ANSI / UL 514C: File No. E30594



NEMA OS 4 – Energy Efficient Air-Sealed Boxes for Electrical Applications



Fire Classification:

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive