



4300-NBK

Four gang electrical box for use with nonmetallic sheathed cable *Replacement for 4300-NB*

Carton Quantity: 18

Mounting Description: Angled mid nails with adjustable

stabilizer bar

Box Type: Wall - Switch/Receptacle

Box Features: Adjustable stabilizing bar, Nails, Speed

"K" nonmetallic clamps

Installation Type: New Work

Height: 3-3/4 in Width: 7-1/2 in Depth: 3 in Volume: 60 cu in Number of Gangs: 4

Product Info

Brand: fiberglassBOX **UPC:** 85339162711 **UNSPSC:** 39121308

Carton Weight: 22 lbs Carton Length: 17 in Carton Width: 16 in Carton Height: 16 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Galvanized steel brackets and plated carbon steel fasteners, Polyvinyl

chloride clamps

Features:

Machine tapped device holes, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

New work residential construction 2 HR fire resistive walls, UL approved for back-to-back installation

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)