



# 4304-NKV

Four gang electrical box for use with nonmetallic

sheathed cable

**Carton Quantity: 18** 

Mounting Description: Angled mid nails

Box Type: Wall - Switch/Receptacle

Box Features: Air-sealed flange (energy efficient), Nails,

Speed "K" nonmetallic clamps

**Installation Type:** New Work

**Height:** 3-3/4 in **Width:** 7-1/2 in **Depth:** 3-9/16 in

Volume: 75 cu in Number of Gangs: 4

## **Product Info**

Brand: Vapor Seal UPC: 85339175582 UNSPSC: 39121308 Carton Weight: 22 lbs

Carton Length: 18 in Carton Width: 16 in Carton Height: 12 in

Country of Origin: United States of America

Color: Off white

**Patents:** U.S. Patent No. 6,908,003 B2 **Material:** Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Polyurethane

flange, Polyvinyl chloride clamps

#### Features:

Machine tapped device holes, slot provision for low voltage divider, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures,

Speed "K" Clamps factory installed

### **Application:**

New work residential construction 2 HR fire resistive walls – air-sealed electrical boxes for envelope walls in Energy Star homes, UL approved for back-to-back installation

#### Standards:

ANSI / UL 514C: File No. E30594



NEMA OS 4 – Energy Efficient Air-Sealed Boxes for Electrical Applications



## **Fire Classification:**

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

## Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)