



## **9380-FANB**

Octagonal steel fan/fixture support box for use with

nonmetallic sheathed cable **Carton Quantity:** 12

Mounting Description: Adjustable bar hanger - 16" to

24" on center joist application

**Box Type:** Ceiling - Fan/Fixture

**Box Features:** Bar hanger **Installation Type:** New Work

Width: 4 in Depth: 1-3/4 in Volume: 17 cu in

Fan Rating: 70lbs
Fixture Rating: 200lbs

# **Product Info**

UPC: 85339975892
UNSPSC: 39121316
Carton Weight: 26 lbs
Carton Length: 16 in
Carton Width: 16 in

Carton Height: 8 in Country of Origin: China

Color: Silver

Material: Galvanized steel

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners

**Box Diameter:** 4

#### Features:

Machine tapped fixture holes, steel box construction, universal bar hanger, steel clamps factory installed.

### **Application:**

New work residential construction 2 HR fire resistive walls and ceilings (70 lbs. fan support and 200 lbs. fixture

support)

**Box Diameter: 4** 

Standards:

ANSI / UL 514A: File No. E487601



### **Fire Classification:**

Fire Test of Building Construction Materials - (Outlet Boxes and Fittings) Metallic Outlet Boxes (QCIT)

Use In Fire-Rated Assemblies

Certified metallic outlet and switch boxes with metallic or nonmetallic cover plates may be used in floor-ceiling and roof-ceiling assemblies with ratings not exceeding 2 h when these assemblies have gypsum wallboard membranes. The boxes are intended to be fastened to the joists with the openings in the wallboard facing cut so that the clearance between the boxes and the gypsum wallboard does not exceed 1/8 in. The boxes are inteded to be installed so that the surface area of individual boxes

does not exceed 16 sq in, and the aggregate surface area of the boxes does not exceed 100 sq in per 100 sq ft of ceiling surface.