



## Product Info

**Brand:** Vapor Seal FlexBOX

**UPC:** 85339984976

**Country of Origin:** United States of America

**Color:** Black

**Patents:** U.S. Patent No. 11050229, U.S. Patent 11075509

**Material:** Polycarbonate

**Additional Materials:** Thermoplastic Polyester Elastomer (TPE)

## P-221NV

Single gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 48

**Mounting Description:** Angled Nails

**Box Type:** Wall - Switch/Receptacle

**Box Features:** Vapor Seal, Nails

**Installation Type:** New Work

**Height:** 3-9/16" in

**Width:** 2-1/4" (Box), 3-1/2" (Vapor Seal) in

**Depth:** 3-7/8" (box), 3-1/2" (Vapor Seal) in

**Volume:** 22 cu in

**Number of Gangs:** 1

## Features:

Thermoplastic Polyester Elastomer (TPE) flange for single drywall offset, Molded-in splined device holes

## Application:

New work residential construction 2 HR fire resistive walls

## Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

## Fire Classification:

### Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*