



P-221NV

Single gang electrical box for use with nonmetallic

sheathed cable

Carton Quantity: 48

Mounting Description: Angled Nails Box Type: Wall - Switch/Receptacle Box Features: Vapor Seal, Nails

Installation Type: New Work

Height: 3-9/16" in

Width: 2-1/4" (Box), 3-1/2" (Vapor Seal) in **Depth:** 3-7/8" (box), 3-1/2" (Vapor Seal) in

Volume: 22 cu in Number of Gangs: 1

Product Info

Brand: Vapor Seal FlexBOX

UPC: 85339984976

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 11050229, U.S. Patent 11075509

Material: Polycarbonate

Additional Materials: Thermoplastic Polyester Elastomer

(TPE)

Features:

Thermoplastic Polyester Elastomer (TPE) flange for single drywall offset, Molded-in splined device holes

Application:

New work residential construction 2 HR fire

resistive walls

Standards:

ANSI / UL 514C: File No. E30594



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 $\frac{1}{2}$ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)