



## **P-442NV**

Two gang VaporSeal® electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 32

**Mounting Description:** Angled mid nails

**Box Type:** Wall - Switch/Receptacle

**Box Features:** Vapor Seal, Nails

**Installation Type:** New Work

**Height:** 4" (Box), 5-1/4" (Vapor Seal) in

**Width:** 3-3/4" (Box), 5" (Vapor Seal) in

**Depth:** 3-14/25" in

**Volume:** 43 cu in

**Number of Gangs:** 2

## **Product Info**

**Brand:** Vapor Seal FlexBOX

**UPC:** 085339 988250

**UNSPSC:** 10085339 988257

**Carton Weight:** 17 lbs

**Carton Length:** 20 in

**Carton Width:** 15 in

**Carton Height:** 15 in

**Country of Origin:** United States of America

**Color:** Black

**Patents:** Patent Pending

**Material:** Polycarbonate

**Additional Materials:** Carbon steel fasteners

## **Features:**

Molded-in splined device holes, Thermoplastic Polyester Elastomer (TPE) flange for single drywall, sealed TPE Clamps, leveling ribs

## **Application:**

New work residential construction 2 HR fire resistive walls

## **Standards:**

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

NEMA OS 4 - Energy Efficient Air-Sealed Boxes for Electrical Applications



**⚠ WARNING - PROP 65**  
[Click here for more information!](#)

## **Fire Classification:**

### **Fire Test of Building Construction Materials**

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

**Fire Resistance Classification in Wall Assemblies 2-Hours or less**

Shall be separated by a horizontal distance of not less than 24 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---