



P-442NV

Two gang VaporSeal® electrical box for use with nonmetallic sheathed cable

Carton Quantity: 32

Mounting Description: Angled mid nails

Box Type: Wall - Switch/Receptacle

Box Features: Vapor Seal, Nails

Installation Type: New Work

Height: 4" (Box), 5-1/4" (Vapor Seal) in

Width: 3-3/4" (Box), 5" (Vapor Seal) in

Depth: 3-14/25" in

Volume: 43 cu in

Number of Gangs: 2

Product Info

Brand: Vapor Seal FlexBOX

UPC: 085339 988250

UNSPSC: 10085339 988257

Carton Weight: 17 lbs

Carton Length: 20 in

Carton Width: 15 in

Carton Height: 15 in

Country of Origin: United States of America

Color: Black

Patents: Patent Pending

Material: Polycarbonate

Additional Materials: Carbon steel fasteners

Features:

Molded-in splined device holes, Thermoplastic Polyester Elastomer (TPE) flange for single drywall, sealed TPE Clamps, leveling ribs

Application:

New work residential construction 2 HR fire resistive walls

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

NEMA OS 4 - Energy Efficient Air-Sealed Boxes for Electrical Applications



⚠ WARNING - PROP 65
[Click here for more information!](#)

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)
