



## Product Info

**UPC:** 85339998707

**UNSPSC:** 39121309

**Carton Weight:** 12.4 lbs

**Carton Length:** 21 in

**Carton Width:** 10 in

**Carton Height:** 11 in

**Country of Origin:** United States of America

**Color:** Black

**Material:** Polyvinyl Chloride

## P-9367

Single gang electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 50

**Box Type:** Wall - Switch/Receptacle

**Installation Type:** New Work

**Height:** 3-1/4 in

**Width:** 2-3/8 in

**Depth:** 1-11/16 in

**Volume:** 16.0 cu in

**Number of Gangs:** 1

### Features:

Quick Thread device holes, leveling ribs, Shallow wall application, sidecar box

### Application:

New work wall construction - side cube body design for use in basement type furring strip shallow walls

### Standards:

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

**⚠ WARNING - PROP 65**

[Click here for more information!](#)

### Fire Classification:

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*