



P-9367

Single gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 50

Closure Type:

Mounting Description: Molded Bracket

Box Type: Wall - Switch/Receptacle

Box Features: Molded Bracket

Installation Type: New Work

Height: 3-1/4 in

Width: 2-3/8 in

Depth: 1-11/16 in

Volume: 16.0 cu in

Number of Gangs: 1

Product Info

Brand: Flexbox

UPC: 85339998707

UNSPSC: 39121309

Carton Weight: 12.4 lbs

Carton Length: 21 in

Carton Width: 10 in

Carton Height: 11 in

Country of Origin: United States of America

Color: Black

Material: Polyvinyl Chloride

Additional Materials:

Features:

Quick Thread device holes, leveling ribs, Shallow wall application, sidecar box

Application:

New work wall construction - side cube body design for use in basement type furring strip shallow walls

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)