



## P-9367

Single gang electrical box for use with nonmetallic

sheathed cable

**Carton Quantity:** 50

Box Type: Wall - Switch/Receptacle

**Installation Type:** New Work

Height: 3-1/4 in

Width: 2-3/8 in

**Depth:** 1-11/16 in **Volume:** 16.0 cu in

Number of Gangs: 1

# **Product Info**

UPC: 8533998707 UNSPSC: 39121309 Carton Weight: 12.4 lbs Carton Length: 21 in Carton Width: 10 in

Carton Height: 11 in

Country of Origin: United States of America

Color: Black

Material: Polyvinyl Chloride

#### Features:

Quick Thread device holes, leveling ribs, Shallow wall application, sidecar box

### **Application:**

New work wall construction – side cube body design for use in basement type furring strip shallow walls

#### Standards:

ANSI / UL 514C: File No. E30594



### Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)