



## P-93670W

Single gang electrical box for use with nonmetallic

sheathed cable

**Carton Quantity:** 50

**Closure Type:** 

Mounting Description: Metal ears

**Box Type:** Wall - Switch/Receptacle **Box Features:** Metal ears

Installation Type: Old Work Height: 3-1/4 in Width: 2-3/8 in Depth: 1-11/16 in

Volume: 16.0 cu in Number of Gangs: 1

# **Product Info**

Brand: Flexbox UPC: 85339698708 UNSPSC: 39121309 Carton Weight: 13.3 lbs

Carton Length: 21 in Carton Width: 10 in Carton Height: 11 in

Country of Origin: United States of America

Color: Black

Material: Polyvinyl Chloride

**Additional Materials:** Galvanized steel brackets and plated

carbon steel fasteners

#### Features:

Quick Thread device holes, leveling ribs, Shallow wall application, sidecar box

#### **Application:**

Old work wall construction – side cube body design for use in basement type furring strip shallow walls

#### Standards:

ANSI / UL 514C: File No. E30594



### Fire Classification:

**Fire Test of Building Construction Materials** 

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)