



## **RD-42V**

Range/dryer/car charger electrical box for use with

nonmetallic sheathed cable **Carton Quantity:** 24

Mounting Description: Nail-on with fetter ring nails

Box Type: Wall - Switch/Receptacle

Box Features: Air-sealed flange (energy efficient), Nails

**Installation Type:** New Work

Height: 3-3/4 in Width: 4 in Depth: 3-13/16 in Volume: 42 cu in

# **Product Info**

Brand: Vapor Seal UPC: 85339129066 UNSPSC: 39121309 Carton Weight: 23 lbs Carton Length: 22 in Carton Width: 9 in

Carton Height: 13 in

Country of Origin: United States of America

Color: Off white

**Patents:** U.S. Patent No. 6,908,003 B2 **Material:** Fiberglass reinforced polyester

**Additional Materials:** Carbon steel fasteners, Plated carbon steel clamp and fasteners, Polyurethane flange

#### Features:

Machine tapped holes for 2-position device , internal metal clamp for easy wire adjustment, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

#### **Application:**

New work residential construction 2 HR fire resistive walls – air tight

#### Standards:

ANSI / UL 514C: File No. E30594



NEMA OS 4 – Energy Efficient Air-Sealed Boxes for Electrical Applications



#### Fire Classification:

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-

### **Hours or less**

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)