



### FB-2N

Rectangular floor box assembly with a nickel plated brass  $% \left( \frac{1}{2}\right) =\frac{1}{2}\left( \frac{1}{2}$ 

duplex device cover **Carton Quantity:** 6

Mounting Description: Metal wing brackets/nonmetal

flange floor or ceiling compression

Box Type: Floor

Installation Type: New Work, Old Work

Height: 4.31 in Width: 2.5 in Depth: 3.5 in Volume: 24.5 cu in

# **Product Info**

UPC: 85339941293 UNSPSC: 39121307 Carton Weight: 9 lbs Carton Length: 24 in Carton Width: 9 in

**Carton Height:** 10 in **Country of Origin:** China

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate box and nickel plated brass cover

**Additional Materials:** Closed cell rubber gasket, Galvanized steel dust plate with plated carbon steel fasteners, Nitrile O-ring, Nonmetallic pop-in cable clamp,

Plated carbon steel fasteners

Cover Finish: Nickel

#### Features:

Designed for use in wood floor construction and can be installed with multiple floor substrate materials, meets scrub-water exclusion test, tamper resistant receptacle, simple exterior shape for easy cut-in application

### **Application:**

Floor box assembly for residential wood floor cut-in application for use with nonmetallic sheathed cable. Used in areas of the home with large floor space openings where additional electric outlets are required by National Electrical Code to minimize long extension cord runs.

## Standards:

ANSI / UL514C: File No. QCMZ.E30594



