



## SB-1

Single gang adjustable electrical box for use with

nonmetallic sheathed cable **Carton Quantity:** 48

**Mounting Description:** 2 Screws **Box Type:** Wall - Switch/Receptacle

Box Features: Adjustable box (SLIDERBOX®), Screws

Installation Type: New Work, Old Work

Height: 3-3/4 in Width: 2-5/16 in Depth: 3-9/16 in Volume: 23 cu in Number of Gangs: 1

## **Product Info**

Brand: SLIDERBOX
UPC: 85339945000
UNSPSC: 39121308
Carton Weight: 14 lbs
Carton Length: 16 in
Carton Width: 10 in

Carton Height: 12 in

Country of Origin: United States of America

Color: Beige

Patents: U.S. Patent No. 7,855,338

**Material:** Polyvinyl Chloride

**Additional Materials:** Carbon steel fasteners, Polycarbonate adjustable mounting plate

#### **Features:**

Molded-in splined device holes, adjustable slider plate for additional wall substrate thickness, rectangular exterior for easy cut-in, leveling ribs, offset gauge marks

#### Application:

New and old work residential construction 2 HR fire resistive walls and ceilings

### **Standards:**

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

# Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be  $4-\frac{1}{2}$  feet from one another

Note: For more details please refer to the UL fire resistive