ALLIED MOULDED PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506

# SB-1H

Single gang adjustable electrical box for use with nonmetallic sheathed cable

**Carton Quantity:** 12

**Mounting Description:** 2 Screws

**Box Type:** Wall - Switch/Receptacle

**Box Features:** Adjustable box (SLIDERBOX®), Screws

**Installation Type:** New Work

**Height:** 2-5/16 in

**Width:** 3-3/4 in

**Depth:** 3-9/16 in

**Volume:** 23 cu in

**Number of Gangs:** 1

## Product Info

**Brand:** SLIDERBOX

**UPC:** 85339945031

**UNSPSC:** 39121308

**Carton Weight:** 4 lbs

**Carton Length:** 15 in

**Carton Width:** 8 in

**Carton Height:** 5 in

**Country of Origin:** United States of America

**Color:** Beige

**Patents:** U.S. Patent No. 7,855,338

**Material:** Polyvinyl Chloride

**Additional Materials:** Carbon steel fasteners, Polycarbonate adjustable mounting plate

**Features:**

Horizontal mount design with molded-in splined device holes, adjustable slider plate for additional wall substrate thickness, rectangular exterior for easy cut-in, leveling ribs, offset gauge marks

**Application:**

New and residential construction 2 HR fire resistive walls and ceilings

**Standards:**

ANSI / UL 514C: File No. E30594

LISTED

**WARNING** – PROP 65
Click here for more information!

**Fire Classification:**

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

**Fire Resistance Classification in Wall Assemblies 2-Hours or less**

Shall be separated by a horizontal distance of not less than 24 inches

**Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less**

Distance between boxes must be 4-½ feet from one another

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*