



## 1096-N

Single gang electrical box for use with nonmetallic

sheathed cable

**Carton Quantity: 100** 

Mounting Description: Angled mid nails

Box Type: Wall - Switch/Receptacle

**Box Features: Nails** 

**Installation Type:** New Work

**Height:** 3-13/16 in **Width:** 2-1/4 in **Depth:** 3 in

Volume: 18 cu in Number of Gangs: 1

# **Product Info**

**Brand:** fiberglassBOX

UPC: 85339244141 UNSPSC: 39121308 Carton Weight: 32 lbs

Carton Length: 21 in Carton Width: 13 in Carton Height: 13 in

Country of Origin: United States of America

Color: Off white

**Material:** Fiberglass reinforced polyester **Additional Materials:** Carbon steel fasteners

#### Features:

Machine tapped device holes, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

## **Application:**

New work residential construction 2 HR fire resistive walls & ceilings, UL approved for back-to-back installation

#### Standards:

ANSI / UL 514C: File No. E30594



## **Fire Classification:**

# Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

## Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive