



1099-N

Single gang electrical box for use with nonmetallic

sheathed cable

Carton Quantity: 100

Mounting Description: Angled mid nails

Box Type: Wall - Switch/Receptacle

Box Features: Nails

Installation Type: New Work

Height: 3-27/32 in Width: 2-1/4 in Depth: 3-9/16 in Volume: 22.5 cu in

Number of Gangs: 1

Product Info

Brand: fiberglassBOX UPC: 85339260004 UNSPSC: 39121308 Carton Weight: 39 lbs Carton Length: 20 in Carton Width: 13 in

Carton Height: 16 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester **Additional Materials:** Carbon steel fasteners

Features:

Machine tapped device holes, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low

temperatures.

Application:

New work residential construction 2 HR fire resistive walls

& ceilings,

UL certified forback-to-back installation

Standards:

ANSI / UL 514C: File No E30594



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 $\frac{1}{2}$ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)